

SPECIFICATIONS

- WO-14: ROTATION LOCK:** **FACTORY INSTALLED ONLY!** A positive locking device for securing the boom at 12-fixed points of rotation while operating the crane. *(Standard on P-20 & M2000)*
- WO-38: 15' PENDANT:** Optional 15' Hand Held Pendant Control. *(Standard 10' Pendant included with crane)*
- WO-39: WIRELESS REMOTE CONTROLL:** Compact, water resistant & equipped with a belt clip. Fifty foot range and a long battery life provide you with the freedom to move about while not being tethered to the crane.
- WA-15: REMOVABLE OUTRIGGER:** A Removable Crank Down Outrigger for added stability and leveling of crane. Useful when crane is used on unlevelled/uneven ground.
- WA-30: WINCH BLOCK:** This accessory is necessary if you desire to use your Western Mule Crane for winching of the vehicle or to winch loads to the vehicle
- WA-34: FOLD-DOWN OUTRIGGER:** A bolt on spring-loaded outrigger for installation on pickups, service bodies or other mobile platforms. ***(Bolts to underbody crane support mount. Not provided).***
- CABLE LENGTH:** Optional cable lengths are available to meet customer specific requirements. Lengths from 25 feet to 100 feet are available. *(Contact factory for maximum available cable capacities)*
- LIFTING LINE:** Optional Stainless Steel Cable and Di-Electric Rope are available.
- PEDESTAL HEIGHT:** **FACTORY INSTALLED ONLY!** The standard height pedestal is 24 inches. The pedestal height can be factory altered to meet specific installation requirements. *(specify height when ordering)*
- 110 VOLT AC POWERED:** **FACTORY INSTALLED ONLY!**
- HAND CRANK POWERED:** **FACTORY INSTALLED ONLY!**