



FOLD - A - WAY
CRANE

OPTIONS & ACCESSORIES

M-Series Cranes:

SPECIFICATIONS

- WO-12: FREE-WHEELING:** This feature offers a tremendous advantage in many lifting or winching situations. On winches equipped with Free-Wheeling, the winch drum may be disengaged from the gears allowing the cable to be freely pulled out to the distance required. *(Not to be installed on models rated for Man-Lift)*
- WO-14: ROTATION LOCK: FACTORY INSTALLED ONLY!** A positive locking device for securing the boom at 12-fixed points of rotation while operating the crane.
- WO-38: 15' PENDANT:** Optional 15' Hand Held Pendant Control. *(Standard 10' Pendant included with crane)*
- WA-15: REMOVABLE OUTRIGGER:** A Removable Crank Down Outrigger for added stability and leveling of crane. Useful when crane is used on unlevelled/uneven ground.
- WA-30: WINCH BLOCK:** This accessory is necessary if you desire to use your Western Mule Crane for winching of the vehicle or to winch loads to the vehicle
- WA-34: FOLD-DOWN OUTRIGGER:** A bolt on spring-loaded outrigger for installation on pickups, service bodies or other mobile platforms. *(Bolts to underbody crane support mount. Not provided).*
- CABLE LENGTH:** Optional cable lengths are available to meet customer specific requirements. Lengths from 25 feet to 100 feet are available. *(Contact factory for maximum available cable capacities)*
- LIFTING LINE:** Optional Stainless Steel Cable and Di-Electric Rope are available.
- PEDESTAL HEIGHT: FACTORY INSTALLED ONLY!** The standard height pedestal is 22 inches. The pedestal height can be factory altered to meet specific installation requirements. *(specify height when ordering)*
- 110 VOLT AC POWERED: FACTORY INSTALLED ONLY!**
- HAND CRANK POWERED: FACTORY INSTALLED ONLY!**

NOTE: CUSTOM CONFIGURATIONS AND OPTIONS ARE AVAILABLE. FOR ADDITIONAL INFORMATION, CALL 1-800-288-6853.