



FOLD - WAY
CRANE

OPTIONS & ACCESSORIES

U-Series Cranes:

SPECIFICATIONS

- WO-02: LEFT (STREET SIDE) MAST POSITION: FACTORY INSTALLED ONLY!** The Cranes Mast can be placed on the street side rather than the standard curbside of the bumper.
- WO-12: FREE-WHEELING:** This feature offers a tremendous advantage in many lifting or winching situations. On winches equipped with Free-Wheeling, the winch drum may be disengaged from the gears allowing the cable to be freely pulled out to the distance required. *(Not to be installed on models rated for Man-Lift)*
- WO-14: ROTATION LOCK: FACTORY INSTALLED ONLY!** A positive locking device for securing the boom at 12-fixed points of rotation while operating the crane.
- WO-15: ROTATION STOPS: FACTORY INSTALLED ONLY!** For limiting rotation of the boom. Stops will be strategically placed to prevent contact of the load with the inner or outer walls of the vehicle.
- WO-17: LOWER ENCLOSURE: FACTORY INSTALLED ONLY!** A Three-piece factory installed aluminum protective cover for the bottom side of the bumper. (This cover is beneficial in adverse climatic conditions. The cover will help in keeping the unit clean and free of mud, dirt, snow, etc.)
- WO-18: TAIL LIGHTS: FACTORY INSTALLED ONLY!** The L.E.D. Tail Lights shall be sealed beam combination stop/tail/turn lights, flush mounted in a heavy-duty rubber shock mount. Pre-Wired into the bumper. (5 year warranty on L.E.D. Light)
- WO-19: BACKUP LIGHTS:** The L.E.D. Backup Lights shall be sealed beam lights, flush mounted in a heavy duty rubber shock mount. The bulb shall be rated at a min. of 32 candlepower. Pre-Wired into the bumper.
- WO-32: LEFT SIDE SWING DOWN OUTRIGGER: FACTORY INSTALLED ONLY!** Optional Left Side Swing Down Outrigger for light duty vehicles and vans, to add increased stability to the vehicle. Western Mule U-Series Cranes are equipped with factory installed Right Side Swing Down Outriggers as standard equipment. .
- WO-38: 15' PENDANT:** Optional 15' Hand Held Pendant Control. *(Standard 10' Pendant included with crane)*
- WO-41: FALL ARRESTOR ATTACHMENT PIN:** Attachment point required for suspending a personnel fall arresting device. (Required when being used as a Man-Lift).l
- WO-60: VISE MOUNT: FACTORY INSTALLED ONLY!** A Swivel Vise Mount, integrated into the rear corner of the bumper. (
- WO-CSR: CONFINED SPACE RESCUE & RECOVERY SYSTEM: FACTORY INSTALLED ONLY!** Required when using the crane as a man-lift for confined space activates. This option includes WO-14 Rotation Lock, WO-41 Fall Arrestor Boom Attachment Anchor Pin, WO-23 65' x 3/16" Galvanized. Lifting Cable (1350 lb cap. models only, 2000 lb cap models ship standard with 50' x 7/32"), R50G Quick attached hand crank operated recovery winch/fall arrestor with 50' lifeline.
- WA-15: REMOVABLE OUTRIGGER:** A Removable Crank Down Outrigger for added stability and leveling of crane. Useful when crane is used on unlevelled/uneven ground.
- WA-30: WINCH BLOCK:** This accessory is necessary if you desire to use your Western Mule Crane for winching of the vehicle or to winch loads to the vehicle

CABLE LENGTH: Optional cable lengths are available to meet customer specific requirements. Lengths from 25 feet to 100 feet are available. *(Contact factory for maximum available cable capacities)*

LIFTING LINE: Optional Stainless Steel Cable and Di-Electric Rope are available.

MAST POSITION AND BOOM HEIGHT: FACTORY INSTALLED ONLY! The Mast and Boom Height can be factory altered to meet a customer's unique lifting requirements. *(contact factory for more information)*

NOTE: CUSTOM CONFIGURATIONS AND OPTIONS ARE AVAILABLE. CONTACT THE FACTORY FOR MORE INFO.